



ECO CANISTER SYSTEM ADHESIVE 22-28



COLOR
Clear/Natural

AVERAGE NONVOLATILE
32-34 %

BONDING TIME
0-6 minutes
The drying time depends on the temperature, humidity and film thickness.

SAFETY
Flammability:
Nonflammable adhesive with non-flammable propellant.

LIMITATIONS
Do not store at temperatures over 120°F. Do not store directly on concrete floor. Not recommended for use on expanded polystyrene, flexible plastics, plasticized vinyls, or high pressure laminates. Test compatibility before using.

WARNING
Use with adequate ventilation, avoid prolonged or repeated breathing of vapors. Contains Methylene Chloride. Refer to (MSDS) Material Safety Data Sheet. Avoid prolong or repeated contact with skin. Do not take internally. In case of Emergency call a physician. Keep out of reach of children.

CLEANUP
Nonflammable solvent

DESCRIPTION
22-28 Eco-Canister System Adhesive is non-flammable solvent based adhesive in a ready to use portable canister for use in sheet metal shops. The adhesive is non-flammable per flame projection test. It is suitable for quick easy bonding of fiberglass to metal, plastics and foils. It is easily sprayed with its specially designed gun and hose assembly.

METHOD OF APPLICATION
Spray

COVERAGE
Approx. 85 – 100 S/F Per Pound

SPECIFICATION COMPLIANCE
ASTM C916 TYPE II

APPLICATION
This product is for industrial use only. It should be applied by trained and qualified craftspeople, Be sure surfaces are clean and dry. When bonding insulation to itself or to sheet metal, apply the adhesive in a thin uniform coat. Press the insulation firmly in place. There is adequate open time for normal shop procedures. After connecting the hose and gun assembly, keep the valve on the canister open and the hose pressurized. DO NOT close valve on canister until ready to connect hose to a new canister.

WARRANTY TERMS: The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change notice. To be sure information is current call Mon-Eco Industries, Inc.

Terms of Warranty: Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE. No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.

MON-ECO INDUSTRIES, INC.

5 JOANNA COURT • EAST BRUNSWICK, NJ 08816
(732) 257-7942 • 800-899-6326 • FAX (732) 257-6525

www.mon-ecoindustries.com