



ECO CANISTER SYSTEM ADHESIVE 22-38

COLOR

Clear

SERVICE TEMPERATURE

-40° to 180° F
(-40° to 82°C)

SPECIFIC GRAVITY

86-89

PERCENT VOC WT.

Less than 80/g./L., Calculated. EPA Method 24

BONDING TIME

2 to 5 minutes

SAFETY

FLAMMABILITY:

Flammable, per industry standard flame projection test. Avoid open flames, sources of ignition high heat.

DOES NOT CONTAIN METHYLENE CHLORIDE

LIMITATIONS

Do not store at temperatures over 120° F. Do not store directly on concrete floor. Not recommended for bonding of expanded polystyrene, flexible plastics, plasticized vinyls, or high pressure laminates. Test compatibility before using.

WARNING

Use with adequate ventilation. Refer to (MSDS) Material Safety Data Sheet. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Do not take internally. In an emergency call a physician. Keep out of reach of children.



DESCRIPTION

22-38 Eco-Canister System Adhesive is Methylene Chloride free. It is a solvent based, fast drying pressure sensitive spray adhesive in a ready to use portable canister for use in sheet metal shops. It is suitable for quick easy bonding of fiberglass to metal. It is also suitable for bonding foam, fabrics, some plastics and foils. It is easily sprayed with its specially designed gun and hose assembly sold separately.

METHOD OF APPLICATION

Spray: Uses specially designed gun and hose.

COVERAGE

Approximately 100- 150 S/F Per Pound

APPLICATION

This product is for industrial use only. It should be applied by trained and qualified craftspeople. Be sure surfaces are clean and dry before application. When bonding insulation to itself or sheet metal apply 22-38 to the surface in a uniform pattern.. Press the insulation firmly in place. There is adequate open time for normal shop procedures. After connecting the hose and gun assembly, confirm that all connections are tight. Keep the valve on the canister open and the hose pressurized. DO NOT close valve on canister until ready to connect hose to a new canister

CLEANUP

Non-Flammable solvent

10/09

WARRANTY TERMS: The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change notice. To be sure information is current call Mon-Eco Industries, Inc.

Terms of Warranty: Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. **WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE.** No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.

MON-ECO INDUSTRIES, INC.

5 JOANNA COURT•EAST BRUNSWICK, NJ 08816 (732) 257-7942 • 800-899-6326 • FAX (732) 257-6525

www.mon-ecoindustries.com

