ECO EVERFLEX SEALANT 44-33

COLOR
Gray

SERVICE TEMPERATURE
-40°F to 200°F

WEIGHT PER GALLON
11.8 lbs.

AVERAGE NON VOLATILE
80% by weight

WATER RESISTANCE
Excellent

DRYING TIME
Non-Hardening (may be used immediately)

SAFETY
Flammability
Wet: Non-flammable
Dry: Self-extinguishing

CAUTION
Although this product is a water system and considered non-hazardous, good handling practices should be observed. Use with ad\equate ventilation. Avoid prolonged or repeated breathing of vapor and contact with skin. Do not take internally.

ASBESTOS FREE

Meets requirements for LEED® IEQ Credit 4.1: Low Emitting Materials: Adhesives & Sealants.
MAX VOC= 0.38 lbs/gal. or 45 grams/liter, less water & exempt solvents.

DESCRIPTION
Eco-Everflex Sealant 44-33 is a specially designed non-hardening fire resistive, water based sealant. Because it is water based it has no offensive solvent odor and is safe to use in occupied areas. This sealant is easily applied by pump or hand extrusion. It does not string or web during or after application. Eco-Everflex Sealant is ideal for sealing Snap-Lock or Pittsburgh Seams on HVAC ductwork. It is suitable for inline application. Because of its high solids, low shrinkage, and Everflex properties, 44-33 is also used as an acoustical sealant.

It presses into voids and gaps between studs and floors and remains flexible to seal these areas against noise penetration during expansion and contraction.

LIMITATIONS
Keep from freezing. Apply between 40°F and 110°F. Not formulated for outside U.V. exposure.

APPLICATION METHOD
Pump or hand extrusion

CLEANUP
Wet: Hot soapy water
Dry: 44-10

07/2017

WARRANTY TERMS: The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change notice. To be sure information is current call Mon-Eco Industries, Inc.
Terms of Warranty: Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE. No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.

MON-ECO INDUSTRIES, INC.
5 JOANNA COURT•EAST BRUNSWICK, NJ 08816 (732) 257-7942 • **800-899-6326** • FAX (732) 257-6525
www.mon-ecoindustries.com

HARDI
HEATING, AIRCONDITIONING & REFRIGERATION DISTRIBUTORS INTERNATIONAL