

# 20-00 Eco-Stuck Contact Cement Zero VOC

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).  
Date of Issue: 11/09/2021 Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** 20-00 Eco-Stuck Contact Cement Zero VOC

#### 1.2. Intended Use of the Product

For professional use only.

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

Mon-Eco Industries, Inc.

5 Joanna Ct.

East Brunswick, NJ 08816

United States

Phone: 732-257-7942

#### 1.4. Emergency Telephone Number

**Emergency Number** : ChemTel LLC  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Flam. Liq. 2 H225

Eye Irrit. 2A H319

STOT SE 3 H336

Aquatic Acute 2 H401

Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

##### GHS-US/CA Labeling

##### Hazard Pictograms (GHS-US/CA)



##### Signal Word (GHS-US/CA)

: Danger

##### Hazard Statements (GHS-US/CA)

: H225 - Highly flammable liquid and vapor.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H401 - Toxic to aquatic life.  
H411 - Toxic to aquatic life with long lasting effects.

##### Precautionary Statements (GHS-US/CA)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take action to prevent static discharges.  
P261 - Avoid breathing vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.

# 20-00 Eco-Stuck Contact Cement Zero VOC

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 - Call a POISON CENTER or doctor if you feel unwell.  
 P337+P313 - If eye irritation persists: Get medical advice/attention.  
 P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.  
 P391 - Collect spillage.  
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 - Store in a well-ventilated place. Keep cool.  
 P405 - Store locked up.  
 P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Acetone	Dimethyl ketone / 2-Propanone / ACETONE / Propan-2-one / Propanone	(CAS-No.) 67-64-1	73.4	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
2-Propenenitrile, polymer with 1,3-butadiene	Polymer, acrylonitrile-butadiene / Butadiene acrylonitrile rubber 170 / Acrylonitrile-butadiene copolymer / Acrylonitrile-butadiene polymer / BUTADIENE/ACRYLONITRILE COPOLYMER / Acrylonitrile-butadiene, copolymer / Butadiene-acrylonitrile copolymer / Acrylonitrile-butadiene copolymer crosslinked with divinylbenzene / Polymer of acrylonitrile/buta-1,3-diene	(CAS-No.) 9003-18-3	13.3	Comb. Dust
Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol	p-tert-Butylphenol-formaldehyde copolymer / Polymer, formaldehyde with 4-(1,1-dimethylethyl)phenol / 4-tert-Butylphenol-formaldehyde polymer / Alkylphenol disulfide / Formaldehyde-p-tert-butylphenol polymer	(CAS-No.) 25085-50-1	13.3	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Comb. Dust
Chromate(1-), bis[1-[(2-hydroxy-5-nitrophenyl)azo]-2-naphthalenolato(2-)]-, hydrogen, compound with N-cyclohexylcyclohexanamine (1:1)	Hydrogen bis[1-[(2-hydroxy-5-nitrophenyl)azo]-2-naphthalato(2-)]chromate(1-), compound with dicyclohexylamine (1:1) / Chromate(1-), bis[1-[(2-(hydroxy-.kappa.O)-5-nitrophenyl)azo-.kappa.N1]-2-naphthalenolato(2-)]-	(CAS-No.) 74421-71-9	< 0.1	Repr. 1B, H360

# 20-00 Eco-Stuck Contact Cement Zero VOC

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

	.kappa.O]-, hydrogen, compound with N-cyclohexylcyclohexanamine (1:1) / Chromate(1-), bis[1-[2-[2-(hydroxy-.kappa.O)-5-nitrophenyl]diazenyl-.kappa.N1]-2-naphthalenolato(2)-.kappa.O]-, hydrogen, compound with N-cyclohexylcyclohexanamine (1:1:1) / Bis[1-[2-[2-(hydroxy-.kappa.O)-5-nitrophenyl]diazenyl-.kappa.N1]-2-naphthalenolato(2)-.kappa.O]chromate(1-), hydrogen compound with N-cyclohexylcyclohexanamine (1:1:1)			
--	---	--	--	--

Full text of H-statements: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Immediately remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause drowsiness and dizziness. Causes serious eye irritation.

**Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Skin Contact:** Prolonged exposure may cause skin irritation.

**Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** Repeated or prolonged skin contact may cause dermatitis and defatting.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. A heavy water stream may spread burning liquid.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Highly flammable liquid and vapor. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

# 20-00 Eco-Stuck Contact Cement Zero VOC

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Smoke.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources first, then ventilate the area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Precautions for Safe Handling:** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, spray. Take precautionary measures against static discharge. Use only non-sparking tools. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

**Incompatible Materials:** Strong oxidizing agents. Alkalis. Amines.

### 7.3. Specific End Use(s)

For professional use only.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Acetone (67-64-1)		
USA ACGIH	ACGIH OEL TWA [ppm]	250 ppm

# 20-00 Eco-Stuck Contact Cement Zero VOC

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

USA ACGIH	ACGIH OEL STEL [ppm]	500 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	BEI (BLV)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift (nonspecific)
USA OSHA	OSHA PEL (TWA) [1]	2400 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) [2]	1000 ppm
USA NIOSH	NIOSH REL (TWA)	590 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL TWA [ppm]	250 ppm
USA IDLH	IDLH [ppm]	2500 ppm (10% LEL)
Alberta	OEL STEL	1800 mg/m <sup>3</sup>
Alberta	OEL STEL [ppm]	750 ppm
Alberta	OEL TWA	1200 mg/m <sup>3</sup>
Alberta	OEL TWA [ppm]	500 ppm
British Columbia	OEL STEL [ppm]	500 ppm
British Columbia	OEL TWA [ppm]	250 ppm
Manitoba	OEL STEL [ppm]	500 ppm
Manitoba	OEL TWA [ppm]	250 ppm
New Brunswick	OEL STEL	1782 mg/m <sup>3</sup>
New Brunswick	OEL STEL [ppm]	750 ppm
New Brunswick	OEL TWA	1188 mg/m <sup>3</sup>
New Brunswick	OEL TWA [ppm]	500 ppm
Newfoundland & Labrador	OEL STEL [ppm]	500 ppm
Newfoundland & Labrador	OEL TWA [ppm]	250 ppm
Nova Scotia	OEL STEL [ppm]	500 ppm
Nova Scotia	OEL TWA [ppm]	250 ppm
Nunavut	OEL STEL [ppm]	750 ppm
Nunavut	OEL TWA [ppm]	500 ppm
Northwest Territories	OEL STEL [ppm]	750 ppm
Northwest Territories	OEL TWA [ppm]	500 ppm
Ontario	OEL STEL [ppm]	500 ppm
Ontario	OEL TWA [ppm]	250 ppm
Prince Edward Island	OEL STEL [ppm]	500 ppm
Prince Edward Island	OEL TWA [ppm]	250 ppm
Québec	VECD (OEL STEL)	2380 mg/m <sup>3</sup>
Québec	VECD (OEL STEL) [ppm]	1000 ppm
Québec	VEMP (OEL TWA)	1190 mg/m <sup>3</sup>
Québec	VEMP (OEL TWA) [ppm]	500 ppm
Saskatchewan	OEL STEL [ppm]	750 ppm
Saskatchewan	OEL TWA [ppm]	500 ppm
Yukon	OEL STEL	3000 mg/m <sup>3</sup>
Yukon	OEL STEL [ppm]	1250 ppm
Yukon	OEL TWA	2400 mg/m <sup>3</sup>
Yukon	OEL TWA [ppm]	1000 ppm

## 8.2. Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

# 20-00 Eco-Stuck Contact Cement Zero VOC

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: No data available
Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: No data available
Upper Flammable Limit	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: No data available
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity:

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

### 10.2. Chemical Stability:

Highly flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

### 10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

### 10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

### 10.5. Incompatible Materials:

Strong oxidizing agents. Alkalis. Amines.

### 10.6. Hazardous Decomposition Products:

Thermal decomposition may produce: Carbon oxides (CO, CO<sub>2</sub>). Smoke.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

# 20-00 Eco-Stuck Contact Cement Zero VOC

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

**LD50 and LC50 Data:**

No additional information available

**Skin Corrosion/Irritation:** Not classified

**Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation.

**Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** Repeated or prolonged skin contact may cause dermatitis and defatting.

### 11.2. Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

Acetone (67-64-1)	
LD50 Oral Rat	5800 mg/kg (Species: Sprague-Dawley)
LD50 Dermal Rabbit	15688 mg/kg
LC50 Inhalation Rat	44 g/m <sup>3</sup>
ATE US/CA (dermal)	15,688.00 mg/kg body weight
ATE US/CA (vapors)	44.00 mg/l/4h
ATE US/CA (dust, mist)	44.00 mg/l/4h

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General:** Toxic to aquatic life with long lasting effects.

Acetone (67-64-1)	
LC50 Fish 1	4144.846 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	1679.66 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	6210 (6210 – 8120) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [2]	12600 (12600 – 12700) mg/l (Exposure time: 48 h - Species: Daphnia magna)

  

Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol (25085-50-1)	
LC50 Fish 1	0.26 mg/l

### 12.2. Persistence and Degradability

20-00 Eco-Stuck Contact Cement Zero VOC	
Persistence and Degradability	May cause long-term adverse effects in the environment.

  

Acetone (67-64-1)	
Persistence and Degradability	Readily biodegradable in water.

### 12.3. Bioaccumulative Potential

20-00 Eco-Stuck Contact Cement Zero VOC	
Bioaccumulative Potential	Not established.

  

Acetone (67-64-1)	
BCF Fish 1	0.69
Partition coefficient n-octanol/water (Log Pow)	-0.24

# 20-00 Eco-Stuck Contact Cement Zero VOC

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Partition coefficient n-octanol/water (Log Kow)	-0.24
---	-------

### 12.4. Mobility in Soil

No additional information available

### 12.5. Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Proper Shipping Name : ACETONE  
Hazard Class : 3  
Identification Number : UN1090  
Label Codes : 3  
Packing Group : II  
Marine Pollutant : Marine pollutant  
ERG Number : 127



### 14.2. In Accordance with IMDG

Proper Shipping Name : ACETONE  
Hazard Class : 3  
Identification Number : UN1090  
Label Codes : 3  
Packing Group : II  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-D  
Marine pollutant : Marine pollutant



### 14.3. In Accordance with IATA

Proper Shipping Name : ACETONE  
Hazard Class : 3  
Identification Number : UN1090  
Label Codes : 3  
Packing Group : II  
ERG Code (IATA) : 3H



### 14.4. In Accordance with TDG

Proper Shipping Name : ACETONE  
Hazard Class : 3  
Identification Number : UN1090  
Label Codes : 3  
Packing Group : II  
Marine Pollutant (TDG) : Marine pollutant



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

20-00 Eco-Stuck Contact Cement Zero VOC	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated)



# 20-00 Eco-Stuck Contact Cement Zero VOC

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

	exposure) Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation
<b>Acetone (67-64-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>CERCLA RQ</b>	5000 lb
<b>2-Propenenitrile, polymer with 1,3-butadiene (9003-18-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>EPA TSCA Regulatory Flag</b>	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
<b>Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol (25085-50-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>EPA TSCA Regulatory Flag</b>	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
<b>Chromate(1-), bis[1-[(2-hydroxy-5-nitrophenyl)azo]-2-naphthalenolato(2-)]-, hydrogen, compound with N-cyclohexylcyclohexanamine (1:1) (74421-71-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	

### 15.2. US State Regulations

<b>Acetone (67-64-1)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

### 15.3. Canadian Regulations

<b>Acetone (67-64-1)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>2-Propenenitrile, polymer with 1,3-butadiene (9003-18-3)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol (25085-50-1)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Chromate(1-), bis[1-[(2-hydroxy-5-nitrophenyl)azo]-2-naphthalenolato(2-)]-, hydrogen, compound with N-cyclohexylcyclohexanamine (1:1) (74421-71-9)</b>
Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 11/09/2021

### Revision

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

### GHS Full Text Phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Repr. 1B	Reproductive toxicity Category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

# 20-00 Eco-Stuck Contact Cement Zero VOC

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H360	May damage fertility or the unborn child
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US)